

EC-1000

CARBON SCRUBBER



The EC-1000 is our most widely used carbon scrubber and provides enough carbon for a wide range of applications. It is ideally suited for varying flow rates and concentrations of organic vapor. It can easily be set up for passive odor control on temporary storage tanks or be used in series for vacuum truck vapor control.

EC-1000 SPECIFICATIONS



RATED FLOW 0 – 1,000 SCFM Maximum
Flow may be reduced based on piping restrictions

CONNECTION TYPE

Inlet	4 in. Female Cam
Outlet	4 in. Male Cam

MEDIA TYPE

Carbon Capacity	1,000 lbs.
Optional Impregnated GAC	Potassium Permanganate Sodium Hydroxide Potassium Hydroxide

PRESSURE VACUUM SETTINGS

Pressure	12 in. Hg
Optional Vacuum Setting	10 in. Hg

SCRUBBER CHAMBER CHARACTERISTICS

Material	Carbon Steel
Coating	6 to 8 mil. Carboline Epoxy
Overall Foot Print	5 ft. x 5 ft. x 7 ft.
Scrubber Chambers	
Active Volume, Total	48 cu. ft.
Shell Height	48 in.
Diameter	45.5 in.

SPECIAL FEATURES

- Complete removal of organic odors
- Requires no electricity
- Excellent for out-of-the-way locations
- Inlet and outlet sample ports
- A low-VOC, water-resistant epoxy coating polymerized with a polyamine-type curing agent
- Temperature and pressure gauges
- Low point drains

Call Envent now at 888-997-9465 or email us at solutions@envent.net



Corporate Headquarters
3220 East 29th Street ■ Long Beach, CA 90806
www.enventcorporation.com
www.vapor-scrubbers.com