EC-5000 CARBON SCRUBBER



The EC-5000 carbon scrubber is great for vacuum truck exhausts and passive odor control on temporary tanks. They are easily transportable with a forklift. The 5,000 lbs. of carbon in this vessel provides lasting efficiencies up to 100%.

EC-5000 SPECIFICATIONS



RATED FLOW 0 – 4,000 SCFM Maximum

Flow may be reduced based on piping restrictions

CONNECTION TYPE

Inlet 10 in. Flange Outlet 10 in. Flange

MEDIA TYPE

Carbon Capacity
Optional Impregnated GAC

Granular Activated Carbon

5,000 lbs.

Potassium Permanganate Sodium Hydroxide Potassium Hydroxide

SCRUBBER CHAMBER CHARACTERISTICS

Material Carbon Steel

Coating 6 to 8 mil. Carboline Epoxy
Overall Foot Print 6 ft. x 7 ft. x 8.6 ft.

Scrubber Chambers

Active Volume, Total 288 cu. ft.
Length 72 in.
Width 72 in.
Height 96 in.

SPECIAL FEATURES

- Complete removal of organic odors
- Requires no electricity
- Inlet and outlet sample ports
- A low-VOC, water-resistant epoxy coating polymerized with a polyamine-type curing agent
- Temperature and pressure guages
- Low point drains

Call Envent now at 888-997-9465 or email us at solutions@envent.net



Corporate Headquarters

3220 East 29th Street Long Beach, CA 90806

www.enventcorporation.com www.vapor-scrubbers.com