



ACTIVATED CARBON SERVICES & SYSTEMS

Total Plant Vapor Control Management™

8 x 30 COAL BASED (EWCARB830)

EWCARB830 is bituminous coal based granular activated carbon. It is used for a wide range of liquid filtration and purification systems. These carbon systems are most notably used for the removal of volatile organic compound from contaminated wastewater stream. EWCARB830 has a high porosity equating to a large surface area and very effective adsorbing hydrocarbon chains.

GENERAL SPECIFICATIONS:

Particle Size	8 X 30 U.S. Mesh
Iodine number	900 mg/g
Hardness (ASTM D 3802)	90%
Moisture as packed (ASTM 2867)	5% max
Ash Content	12% max
Bulk Density	29-33 lb/ft ³
Apparent Density (ASTM D 3854)	0.47 - 0.53g/cc
Surface Area (BET)	900 m ² /gr

PACKAGING:

200 pound fiber drums, or
1,000 pound bulk sacks

CAUTION: Wet activated carbon removes oxygen from air causing a severe hazard to workers inside carbon vessels. Confined space/low oxygen procedures should be put in place before any entry is made. Such procedures should comply with all applicable Local, State and Federal guidelines.

Call Envent now at 888-997-9465 or email us at solutions@envent.net



Corporate Headquarters
3220 East 29th Street ■ Long Beach, CA 90806
www.enventcorporation.com
www.vapor-scrubbers.com